

RECOMMENDED ASSEMBLY TORQUES

Recommended Assembly Torques - Class 4.6

Property Class 4.6 Commercial Low Tensile Bolts



AS 1111.1

Diameter	Bolt Tension Corresponding to 65% of Proof Load		Breaking Load of Bolt (Min)	
	mm	kN	lbf	Nm
5	2.08	468	2.1	1.5
6	2.94	660	3.5	2.5
8	5.34	1200	8.5	6.3
10	8.45	1900	17	12
12	12.4	2790	30	22
14	16.8	3780	47	35
16	22.9	5150	73	54
18	28.1	6320	101	75
20	35.8	8050	143	106
22	44.3	9960	195	145
24	51.6	11600	248	183
27	67	15060	362	265
30	81.9	18410	491	362
33	101	22800	669	495
36	120	26980	864	637
39	143	32150	1115	820
42	164	36870	1378	1020
48	215	48330	2064	1520
56	298	66990	3338	2460
64	393	88350	5030	3710

Recommended Assembly Torques - BSW

BSW Low Tensile Bolts



AS/NZS 2451

Diameter & Thread		Induced Bolt Preload or Tension Corresponding to 65% of Yield Load	Recommended Assembly Torque to Give induced Preload Equal to 65% of Yield Load
		lbf	lbft
1/4	BSW	750	3
5/16	BSW	1230	6
3/8	BSW	1820	12
7/16	BSW	2480	19
1/2	BSW	3250	28
5/8	BSW	5300	55
3/4	BSW	7830	98
7/8	BSW	10200	150
1	BSW	13300	230
1.1/8	BSW	16700	320
1.1/4	BSW	21500	450
1.1/2	BSW	30800	780

The torques listed are for plain finish (uncoated) fasteners as supplied.

For more technical support, please contact your local **United Fasteners** branch

The content is owned and the copyright of United Fasteners Australia Pty Ltd.

Recommended Assembly Torques - Grade 5

Grade 5 Unified High Tensile Bolts (Same as SAE J429 Grade 5)



Diameter & Thread		Induced Bolt Preload or Tension Corresponding to 65% of yield Load		Recommended Assembly Torque to Give induced Preload Equal to 65% of Yield Load	
		lbf		lbft	
1/4	UNF	2020		8	
5/16	UNF	3190		17	
3/8	UNF	4840		30	
7/16	UNF	6570		48	
1/2	UNF	8840		74	
5/8	UNF	14170		150	
3/4	UNF	20610		360	
7/8	UNF	28150		410	
1	UNF	36660		610	
1/4	UNC	1760		7	
5/16	UNC	2890		15	
3/8	UNC	4290		27	
7/16	UNC	5880		43	
1/2	UNC	7870		66	
5/8	UNC	12480		130	
3/4	UNC	18400		230	
7/8	UNC	25550		370	
1	UNC	33480		560	

The torques listed are for plain finish (uncoated) fasteners as supplied.

Recommended Assembly Torques - Grade 8

Grade 5 Unified High Tensile Bolts (Same as SAE J429 Grade 8)



Diameter & Thread		Induced Bolt Preload or Tension Corresponding to 65% of yield Load		Recommended Assembly Torque to Give induced Preload Equal to 65% of Yield Load	
		lbf		lbft	
1/4	UNF	2830		12	
5/16	UNF	4520		23	
3/8	UNF	6830		43	
7/16	UNF	9230		67	
1/2	UNF	12500		104	
5/8	UNF	19960		207	
3/4	UNF	29120		363	
7/8	UNF	39720		577	
1	UNF	51740		859	
1/4	UNC	2470		10	
5/16	UNC	4100		21	
3/8	UNC	6050		38	
7/16	UNC	8320		60	
1/2	UNC	11050		92	
5/8	UNC	17620		183	
3/4	UNC	26070		325	
7/8	UNC	36010		523	
1	UNC	47200		785	

The torques listed are for plain finish (uncoated) fasteners as supplied.

Recommended Assembly Torques - Class 8.8

Property class 8.8 High Tensile Bolts, ISO Coarse Series Threads



AS 1110.1

Diameter	Bolt Tension Corresponding to 65% of Proof Load		Recommended Assembly Torque	
	mm	kN	lbf	Nm
5	5.4	1210	5	4
6	7.6	1710	9	7
8	13.8	3100	22	16
10	21.9	4920	44	32
12	31.8	7150	77	57
14	43.4	9680	121	90
16	59.2	13310	190	140
18	74.8	16690	269	198
20	95.6	21490	370	270
22	118	26390	520	380
24	138	31020	640	470
27	177	39480	955	700
30	219	49230	1310	970
33	270	60330	1785	1320
36	319	71710	2300	1690
(39)	380	84980	2970	2190
(42)	437	98240	3670	2710
(48)	573	128820	5500	4060
(56)	792	178050	8870	6540
(64)	1045	234930	13380	9870

() Sizes not covered in standard.
Data for sizes above this is given for information only.
The torques listed are for plain finish (uncoated) fasteners as supplied.

Recommended Assembly Torques - Class 10.9

Property class 10.9 High Tensile Bolts



AS 1110.1

Diameter	Bolt Tension Corresponding to 65% of Proof Load		Recommended Assembly Torque	
	mm	kN	lbf	Nm
5	7.67	1720	8	6
6	10.86	2440	13	10
8	19.76	4440	32	12
10	31.27	7030	63	46
12	45.5	10230	109	81
14	62	13960	175	130
16	84.5	19000	270	200
18	103	23160	370	275
20	131.95	36900	528	390
22	164	42820	720	530
24	190.45	55750	915	675
27	248	68100	1340	990
30	302.9	83410	1820	1340
33	371	99070	2450	1810
36	440.7	99070	3170	2340
39	527	118470	4110	3030

The torques listed are for plain finish (uncoated) fasteners as supplied.